

SN 10/657,863

Page 2

IN THE CLAIMS

Please reconsider the claims as follows:

1. (currently amended) An optical monitor, comprising:
a tunable filter for filtering a tapped portion of an optical signal at a predetermined frequency to provide thereby a first filtered optical signal;
a directing means for directing the first filtered optical signal back through the tunable filter to provide thereby a second filtered optical signal; and
a single photodetector for measuring the power of the second filtered optical signal.
2. (currently amended) The optical monitor of claim 1, further comprising an optical coupler for tapping a portion of the optical signal and for directing said second filtered optical signal to said photodetector, wherein said filtered optical signal is directed back through the tunable filter and the optical coupler by said directing means.
3. (currently amended) The optical monitor of claim 2, wherein said optical coupler comprises a 5/95 optical coupler has associated with it a splitting ratio in range from about 1/99 to about 5/99.
4. (currently amended) The optical monitor of claim 2, wherein said optical coupler comprises a multi-section optical coupler.
5. (cancelled)
6. (original) The optical monitor of claim 1, wherein said directing means comprises a mirror.
7. (original) The optical monitor of claim 1, wherein said directing means comprises a Sagnac loop.
8. (currently amended) The optical monitor of claim 1, wherein said directing means is adapted for reducing also substantially eliminates any polarization dependence of [[the]] a reflected portion of the first filtered optical signal.

SN 10/657,863

Page 3

9. (original) The optical monitor of claim 8, wherein said directing means comprises a Faraday rotator mirror.
10. (original) The optical monitor of claim 8, wherein said directing means comprises a quarter-wave plate.
11. (currently amended) The optical monitor of claim 1, further comprising a control unit for tuning said tunable filter across ~~[[the]]~~ a frequency band of the optical signal and ~~recording the monitoring said optical~~ power measured by said photodetector as a function of ~~[[the]]~~ a tuning frequency of said tunable filter.
12. (original) The optical monitor of claim 1, wherein said tunable filter comprises a plurality of coupled Mach-Zehnder Interferometer filters.
13. (original) The optical monitor of claim 12, wherein each of said Mach-Zehnder Interferometer filters comprises at least one phase shifter.
14. (currently amended) The optical monitor of claim 12 ~~[[1]]~~, wherein said tunable filter comprises seven coupled Mach-Zehnder Interferometer filters.
15. (currently amended) The optical monitor of claim 1 ~~[[14]]~~, wherein said tunable filter comprises an exponential distribution of a free-spectral range from 200 to 12800 GHz.
16. (currently amended) A method of ~~optical~~ monitoring an optical signal, comprising:
a) filtering a tapped portion of ~~[[an]]~~ the optical signal at a predetermined frequency using a frequency tunable filter to provide thereby a first filtered optical signal;
b) substantially eliminating ~~[[any]]~~ polarization dependence of the ~~tapped-first filtered optical signal~~;
c) reflecting the first filtered optical signal back through the tunable filter to provide thereby a second filtered optical signal; ~~filtering again, the filtered optical signal~~;
d) determining the power of the second filtered optical signal; and

SN 10/657,863

Page 4

e) repeating steps a) through d) ~~for each frequency~~ throughout a ~~[[the]]~~ frequency band of the optical signal to determine an optical spectrum of the optical signal.

17. (currently amended) An optical monitor, comprising:

a first means for tapping a portion of an optical signal;

a frequency tunable means for filtering a tapped portion of an optical signal at a predetermined frequency to provide thereby a first filtered optical signal;

a second means for reflecting the first filtered optical signal back through the frequency tunable means for filtering and the first means for tapping to provide thereby a second filtered optical signal; and

a third means for measuring the optical power of [[said]] the second filtered optical signal.

18. (cancelled)

19. (currently amended) The optical monitor of claim 17, wherein the second means is adapted for reducing further comprising a means for substantially eliminating any polarization dependence of [[the]] a reflected portion of the first filtered tapped optical signal.

20. (cancelled)

21. (currently amended) The optical monitor of claim 17, further comprising a forth means for scanning a tuning frequency of said tunable means across [[the]] a frequency band of the optical signal and for recording the monitoring the optical power measured by said measuring means as a function of the tuning frequency of said tunable means for filtering.